



For the DIP-switch, choose the rail.

Suspension kit
(included)



AT - 1230 Wien · Isoppgasse 22
T 0664 4554227 · F (01) 318 0567
LED.at@aon.at · www.LED-brenner.at



	S1	S2		S1	S2	Lumen
1			0	0	6100lm	
1			0	1	7500lm	
1			1	0	8700lm	
1			1	1	9900lm	



	Reference	EAN Code	Cover / Material	Color temperature	Luminous flux	Efficiency	Power	Beam angle	Working voltage	Connection	LED	Guarantee / Lifespan	Dimensions	Packing details
30°	LLD70CWS5	8436546697251	White / Aluminum + Polycarbonate	5000K	Max. 9900lm	141lm/W	Max. 70W	30°	180-240VAC 50~60Hz	L-N (max 25 uts)	SAMSUNG SPMWH12228	5 years / >50000h	(L)1437mm (W)68mm (H)74mm	10Uts/box (L)1474mm x (W)390mm x (H)220mm
	LLD70NWS5	8436546697268		4000K	Max. 9900lm	141lm/W							2,8Kg	24Kg
60°	LLD70CWN5	8436546697275	White / Aluminum + Polycarbonate	5000K	Max. 9900lm	141lm/W	Max. 70W	60°	180-240VAC 50~60Hz	L-N (max 25 uts)	SAMSUNG SPMWH12228	5 years / >50000h	(L)1437mm (W)68mm (H)74mm	10Uts/box (L)1474mm x (W)390mm x (H)220mm
	LLD70NWN5	8436546697282		4000K	Max. 9900lm	141lm/W							2,8Kg	24Kg
90°	LLD70CWW5	8436546697299	White / Aluminum + Polycarbonate	5000K	Max. 9900lm	141lm/W	Max. 70W	90°	180-240VAC 50~60Hz	L-N (max 25 uts)	SAMSUNG SPMWH12228	5 years / >50000h	(L)1437mm (W)68mm (H)74mm	10Uts/box (L)1474mm x (W)390mm x (H)220mm
	LLD70NWW5	8436546697305		4000K	Max. 9900lm	141lm/W							2,8Kg	24Kg
Asymmetric	LLD70CWA5	8436546697312	White / Aluminum + Polycarbonate	5000K	Max. 9900lm	141lm/W	Max. 70W	Asymmetric	180-240VAC 50~60Hz	L-N (max 25 uts)	SAMSUNG SPMWH12228	5 years / >50000h	(L)1437mm (W)68mm (H)74mm	10Uts/box (L)1474mm x (W)390mm x (H)220mm
	LLD70NWA5	8436546697329		4000K	Max. 9900lm	141lm/W							2,8Kg	24Kg
Double asymmetric	LLD70CW2A5	8436546697336	White / Aluminum + Polycarbonate	5000K	Max. 9900lm	141lm/W	Max. 70W	Double asymmetric	180-240VAC 50~60Hz	L-N (max 25 uts)	SAMSUNG SPMWH12228	5 years / >50000h	(L)1437mm (W)68mm (H)74mm	10Uts/box (L)1474mm x (W)390mm x (H)220mm
	LLD70NW2A5	8436546697343		4000K	Max. 9900lm	141lm/W							2,8Kg	24Kg

Suspension kit
(included)




AT - 1230 Wien · Isoppgasse 22
T 0664 4554227 · F (01) 318 0567
LED.at@aon.at · www.LED-brenner.at

A close-up photograph of a network switch port. A patch cord with a RJ45 connector is plugged into the port. The switch faceplate shows the port number '21' and a label 'RJ45 Cat 5E 10/100/1000'. The patch cord is a standard Ethernet cable with a blue RJ45 connector.



	S1	S2		S1	S2	Lumen
1			0	0		6100lm
1			0	1		7500lm
1			1	0		8700lm
1			1	1		9900lm



	Reference	EAN Code	Cover / Material	Color temperature	Luminous flux	Efficiency	Power	Beam angle	Working voltage	Connection	LED	Guarantee / Lifespan	Dimensions	Packing details
30°	LLD70CWS7	8436546697350	White / Aluminum + Polycarbonate	5000K	Max. 9900lm	141lm/W	Max. 70W	30°	180-240VAC 50~60Hz	L-N (max 25 uts)	SAMSUNG SPMWH12228	5 years / >50000h	(L)1437mm (W)68mm (H)74mm 2,8Kg	10Outs/box (L)1474mm x (W)390mm x (H)220mm 24Kg
	LLD70NWS7	8436546697367		4000K	Max. 9900lm	141lm/W								
60°	LLD70CWN7	8436546697374	White / Aluminum + Polycarbonate	5000K	Max. 9900lm	141lm/W	Max. 70W	60°	180-240VAC 50~60Hz	L-N (max 25 uts)	SAMSUNG SPMWH12228	5 years / >50000h	(L)1437mm (W)68mm (H)74mm 2,8Kg	10Outs/box (L)1474mm x (W)390mm x (H)220mm 24Kg
	LLD70NWN7	8436546697381		4000K	Max. 9900lm	141lm/W								
90°	LLD70CWW7	8436546697398	White / Aluminum + Polycarbonate	5000K	Max. 9900lm	141lm/W	Max. 70W	90°	180-240VAC 50~60Hz	L-N (max 25 uts)	SAMSUNG SPMWH12228	5 years / >50000h	(L)1437mm (W)68mm (H)74mm 2,8Kg	10Outs/box (L)1474mm x (W)390mm x (H)220mm 24Kg
	LLD70NWW7	8436546697404		4000K	Max. 9900lm	141lm/W								
Asymmetric	LLD70CWA7	8436546697411	White / Aluminum + Polycarbonate	5000K	Max. 9900lm	141lm/W	Max. 70W	Asymmetric	180-240VAC 50~60Hz	L-N (max 25 uts)	SAMSUNG SPMWH12228	5 years / >50000h	(L)1437mm (W)68mm (H)74mm 2,8Kg	10Outs/box (L)1474mm x (W)390mm x (H)220mm 24Kg
	LLD70NWA7	8436546697428		4000K	Max. 9900lm	141lm/W								
Double asymmetric	LLD70CW2A7	8436546697435	White / Aluminum + Polycarbonate	5000K	Max. 9900lm	141lm/W	Max. 70W	Double asymmetric	180-240VAC 50~60Hz	L-N (max 25 uts)	SAMSUNG SPMWH12228	5 years / >50000h	(L)1437mm (W)68mm (H)74mm 2,8Kg	10Outs/box (L)1474mm x (W)390mm x (H)220mm 24Kg
	LLD70NW2A7	8436546697442		4000K	Max. 9900lm	141lm/W								